

Xerox® B310 Printer and Xerox® B305/B315 Multifunction Printer



Finally, printers that can keep up with you.



B310 Printer



B305 Multifunction Printer



B315 Multifunction Printer

SYSTEM SPECIFICATION	XEROX B310 PRINTER	XEROX B305 MULTIFUNCTION PRINTER	XEROX B315 MULTIFUNCTION PRINTER
PRINT SPEED (UP TO:)			
One-sided Speed¹ – B&W Letter (8.5 x 11 in) A4 (210 x 297 mm)	42 ppm 40 ppm	40 ppm 38 ppm	42 ppm 40 ppm
Two-sided Speed¹ – B&W Letter (8.5 x 11 in) A4 (210 x 297 mm)	18 ppm 18 ppm	17 ppm 17 ppm	18 ppm 18 ppm
Monthly Duty Cycle² (Up To:) Pages Per Month	80,000		
Recommended Average Monthly Print Volume (Up To:) Pages Per Month	6,000		
Processor/Memory Clock Speed/Cores Memory	1 GHz Dual Core Processor 256MB RAM	1 GHz Dual Core Processor 512MB RAM	
Connectivity Device Connectivity	Hi Speed USB 2.0 (Type B), Ethernet 10/100 BaseTX, Wireless 802.11 b/g/n	Hi Speed USB 2.0 (Type B), Ethernet 10/100 BaseTX, Wireless 802.11 b/g/n, Hi Speed USB 2.0 (Type A - Thumbdrive)	Hi Speed USB 2.0 (Type B), Ethernet 10/100 BaseTX, Wireless 802.11 b/g/n, Hi Speed USB 2.0 (Type A - Thumbdrive)
Imaging Technology	Monochrome Laser		
PRINT AND COPY			
Print Resolution (Up To:)	600 x 600 dpi, 2400 Image Quality		
Copy Resolution (Up To:)	N/A	600 x 600 dpi	
First-print-out Time (As Fast As:)	5.2 seconds	5.8 seconds	
First-copy-out Time (As Fast As:)	N/A	5.3 seconds	
Page Description Languages	PostScript® 3 Emulation, PCL® 5 / PCL 6 Emulation, Direct Image		
Print Features³	One Touch UI, Print Quality, Normal, Secure, Saved and Sample Set Job Types, Duplex, Orientation, Collation, Print Job ID in Margins, Draft Mode, N-up, Booklet Layout, Watermark, Tray and Toner Status, Rotate Image 180 Degrees, Saved Settings, Earth Smart Settings		
MOBILE AND CLOUD READY			
Mobile Printing	Apple AirPrint, Mopria Print Service, Chromebook, Wi-Fi Direct®		
Mobile Scanning	Apple AirPrint, Mopria Scan Service		
Xerox® Workplace Suite and Xerox® Workplace Cloud	Yes		
Cloud Connectivity	Yes (via Xerox Print and Scan Experience)		

Xerox B310 Printer and Xerox B305/B315 Multifunction Printer

SYSTEM SPECIFICATION	XEROX B310 PRINTER	XEROX B305 MULTIFUNCTION PRINTER	XEROX B315 MULTIFUNCTION PRINTER
SCAN			
Destinations	N/A	USB Drive, Email, FTP, Network or USB Connected Computer, Windows Network Folder	
File Formats	N/A	TIFF, JPG, PDF (non-searchable), Secure PDF, Archival PDF/A	
FAX			
Standard Features	N/A	Fax Preservation, Color Fax, All Sizes Supported (including mixed Letter/Legal/A4), Touch Tone/Pulse, Fax Cover Page, Max Speed, Delayed Send, Block Junk/Banned Fax List, Fax Shortcuts, Broadcast Fax (<400 locations)	
PRINT DETAILS			
First-print-out Time – B&W (As Fast As:)	5.2 seconds	5.8 seconds	
Resolution (Up To:)	600 x 600 dpi, 2400 Image Quality		
Page Description Languages	PostScript® 3 Emulation PCL® 5/PCL 6 Emulation Direct Image		
Unprintable Page Margin	5 mm from each edge		
Print from USB	N/A	File Formats: PDF, JPEG, TIFF, GIF, BMP, PNG, PCX	
Print Driver Types/Operating Systems	Windows® 8, 8.1 Update 1, 10, 11. Windows Server® 2008 SP2 (32- and 64-bit), Windows Server 2008 R2 SP1, Windows Server 2012, Windows Server 2012 R2, Windows Server 2019, macOS 10.14, 10.15, 11, 12. For more information about supported Operating Systems, please visit our Drivers & Downloads page and specify your device at support.xerox.com		
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD-Print 802.1x, SNMP		
Font Capability	PCL6 89 scaleable fonts, 2 bitmapped PS emulation 158 scaleable fonts		
COPY DETAILS			
First-copy-out Time – B&W (As Fast As:)	N/A	5.3 seconds	
Simplex Speed (Up To:)	N/A	40 Letter ppm/38 A4 ppm	42 Letter ppm/39 A4 ppm
Duplex Speed (Up To:)	N/A	17 Letter ppm/17 A4 ppm	18 Letter ppm/18 A4 ppm
Sides (Input:Output)	N/A	1:1, 1:2	1:1, 1:2, 2:1, 2:2
Quantity	N/A	1 to 9,999	
Resolution	N/A	600 x 600 dpi, 300 x 600 dpi	
Reduction/Enlargement	N/A	-25% to 400%	
Copy Features	N/A	N-up, 2-up, 4-up, duplex long edge/short edge binding	
SCAN DETAILS			
Technology	N/A	Color Flatbed Scanner with ADF, Contact Image Sensor (CIS) LED	
Capability	N/A	ADF, up to 50 sheets of 20 lb bond/75 gsm color/B&W. Maximum document stack height 6.5 mm.	Single-pass DADF, up to 50 sheets of 20 lb bond/75 gsm color/B&W. Maximum document stack height 6.5 mm.
Input Speed – Color (Up To:)	N/A	21 ipm simplex letter, 20 ipm simplex A4	21 ipm simplex/42 ipm duplex letter, 20 ipm simplex/40 ipm duplex A4
Input Speed – B&W (Up To:)	N/A	48 ipm simplex letter, 46 ipm simplex A4	48 ipm simplex/96 ipm duplex letter, 46 ipm simplex/92 ipm duplex A4
Resolution	N/A	600 x 600 dpi (ADF) color and B&W	
Resolution (Software Utilities)	N/A	150 x 150, 200 x 200, 300 x 300, 400 x 400, 600 x 600	
Bit Depth	N/A	1 bit B&W, 24 bit color	
Maximum Scan Area (ADF) (in)	N/A	Legal (8.5 x 14 in)	
Maximum Scan Area (ADF) (mm)	N/A	216 x 356 mm	
Maximum Scan Area (Platen) (in)	N/A	8.5 x 11.7 in	
Maximum Scan Area (Platen) (mm)	N/A	216 mm x 297 mm	
Media Weight (ADF)	N/A	16 to 24 lb bond/60 to 90 gsm	
File Formats	N/A	TIFF, JPEG, PDF (non-searchable), Secure PDF, Archival PDF/A	
Supported Scan Destinations	N/A	Email, Front-side USB Drive, FTP, Network or USB Connected Computer, Windows Network Folder	
Scan Driver Compatibility	N/A	TWAIN, WIA, ICA	

Xerox B310 Printer and Xerox B305/B315 Multifunction Printer

SYSTEM SPECIFICATION	XEROX B310 PRINTER	XEROX B305 MULTIFUNCTION PRINTER	XEROX B315 MULTIFUNCTION PRINTER
FAX DETAILS			
Fax Speed	N/A		Max is 33,600 bps, V.34 Half-Duplex Kbps
Memory	N/A		6MB
Resolution (dpi)	N/A		B&W Standard, Fine, Superfine, Ultrafine 200 x 100 Send to 600 x 600 Send Color Fine, Superfine 200 x 200 (Send) and 300 x 200 Send/receive
Compression	N/A		T.4 1D Modified Huffman Encoding T.4 2D Modified Read Encoding T.6 Modified Modified Read Encoding T.85 JBIG T.88 JBIG2 T.81 JPEG
Fax Features	N/A		Auto Answer, Auto Redial, Auto Reduction, Broadcast Send, Junk Fax Filter, Fax Address Book
Fax Forward Destinations	N/A		Fax – using one Fax Shortcut Email – using one Email Shortcut FTP – using one FTP Shortcut
DEVICE MANAGEMENT			
Device Management	Remote Console, Embedded Web Server, Xerox Easy Assist		
Xerox® CentreWare® Web Software	Yes		
SECURITY			
Security Protocols/Features	Digitally Signed Firmware Updates, Certificate Management, Secure Password Reset, TCP Connection Filtering, Port Filtering, Access Controls, Confidential Print, Non-Volatile Memory Wipe, Fax/Network Separation, Protected USB Ports, Auto-insertion of Sender's Email Address, Login Restrictions, TLS 1.3		
WI-FI SECURITY			
Authentication and Encryption Methods	WMM® Wi-Fi Multimedia, Wi-Fi Protected Setup™, Infrastructure (BSS) Mode, WPA Personal TKIP PSK (63 char, 64 ASCII), WPA Enterprise, WPA3 Personal, WPA3 Enterprise; EAP-MD5, EAP-MSCHAPv2, EAP-TLS, EAP-TTLS (CHAPS/IMSCHAPv2/PAP), LEAP, PEAP		
PAPER HANDLING			
AUTOMATIC DOCUMENT FEEDER			
Type of ADF	N/A	Automatic Document Feeder (ADF)	Single-Pass Duplex Automatic Document Feeder (DADF)
Capacity (Up To:)	N/A	50 sheets of 20 lb bond/75 gsm	
Minimum Media Size (in)	N/A	4.1 x 5.8 in	
Minimum Media Size (mm)	N/A	A6 SEF (105 x 148 mm)	
Maximum Media Size (in)	N/A	Legal (8.5 x 14 in)	
Maximum Media Size (mm)	N/A	216 x 355 mm	
Minimum Media Weight (gsm)	N/A	16 lb bond/60 gsm	
Minimum Media Weight – Duplex (gsm)	N/A	N/A	24 lb bond/90 gsm
Maximum Media Weight (gsm)	N/A	24 lb bond/90 gsm	
Maximum Media Weight – Duplex (gsm)	N/A	N/A	24 lb bond/90 gsm
PLATEN			
Maximum Media Size (in)	N/A	8.5 x 11.7 in	
Maximum Media Size (mm)	N/A	A4 (216 x 297 mm)	

Xerox B310 Printer and Xerox B305/B315 Multifunction Printer

SYSTEM SPECIFICATION	XEROX B310 PRINTER	XEROX B305 MULTIFUNCTION PRINTER	XEROX B315 MULTIFUNCTION PRINTER
PAPER HANDLING (CONTINUED)			
MULTIPURPOSE FEEDER			
Standard/Optional	Standard		
Capacity (Up To:)	100 sheets of 20 lb bond/75 gsm		
Minimum Media Size (in)	3.9 x 5.8 in		
Minimum Media Size (mm)	99 x 148 mm		
Maximum Media Size (in)	Legal (8.5 x 14 in)		
Maximum Media Size (mm)	216 x 356 mm		
Minimum Media Weight (gsm)	60 gsm		
Minimum Media Weight – Duplex (gsm)	60 gsm		
Maximum Media Weight (gsm)	217 gsm		
Maximum Media Weight – Duplex (gsm)	90 gsm		
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Card Stock, Labels (Paper Labels), Envelopes, Colored Paper, Letterhead, Preprinted, Bond, Glossy, Rough/Cotton, Recycled		
MAIN TRAY			
Standard/Optional	Standard		
Capacity (Up To:)	250 sheets of 20 lb bond/75 gsm		
Minimum Media Size (in)	3.9 x 5.8 in		
Minimum Media Size (mm)	99 x 148 mm		
Maximum Media Size (in)	Legal (8.5 x 14 in)		
Maximum Media Size (mm)	216 x 356 mm		
Minimum Media Weight (gsm)	60 gsm		
Minimum Media Weight – Duplex (gsm)	60 gsm		
Maximum Media Weight (gsm)	120 gsm		
Maximum Media Weight – Duplex (gsm)	90 gsm		
Media Types Supported	Plain Paper, Cardstock, Recycled, Labels (Paper), Bond, Envelopes, Rough Envelopes, Letterhead, Pre-printed, Colored paper, Light Paper, Heavy Paper, Rough Cotton		
550 SHEET TRAY			
Standard/Optional	Optional		
Capacity (Up To:)	550 sheets of 20 lb bond/75 gsm		
Minimum Media Size (in)	3.9 x 5.8 in		
Minimum Media Size (mm)	99 x 148 mm		
Maximum Media Size (in)	Legal (8.5 x 14 in)		
Maximum Media Size (mm)	216 x 356 mm		
Minimum Media Weight (gsm)	60 gsm		
Minimum Media Weight – Duplex (gsm)	60 gsm		
Maximum Media Weight (gsm)	120 gsm		
Maximum Media Weight – Duplex (gsm)	90 gsm		
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Card Stock, Labels (Paper Labels), Envelopes, Colored Paper, Letterhead, Preprinted, Bond, Glossy, Rough/Cotton, Recycled		
STANDARD/MAXIMUM INPUT CAPACITY			
Standard Input Capacity	350 sheets of 20 lb bond/75 gsm		
Maximum Input Capacity	900 sheets of 20 lb bond/75 gsm		
OUTPUT CAPACITY			
Output Capacity	Up to 150 sheets of 20 lb bond/75 gsm		

Xerox B310 Printer and Xerox B305/B315 Multifunction Printer

SYSTEM SPECIFICATION	XEROX B310 PRINTER	XEROX B305 MULTIFUNCTION PRINTER	XEROX B315 MULTIFUNCTION PRINTER
DEVICE SPECIFICATIONS			
ELECTRICAL REQUIREMENTS			
North America	Voltage: 100 to 127 VAC 47 to 63 hertz (Hz) nominal Frequency: 47 to 63 Hz		
Europe	Voltage: 220 to 240 VAC Frequency: 47 to 63 Hz		
POWER CONSUMPTION			
Operation/Running – 110V	Simplex 570W/Duplex 305W	Simplex 530W/Duplex 315W	Simplex 580W/Duplex 330W
Operation/Running – 220V	Simplex 570W/Duplex 305W	Simplex 530W/Duplex 315W	Simplex 580W/Duplex 330W
Standby Mode – 110V	4.9W	6.5W	7.5W
Standby Mode – 220V	4.9W	6.5W	7.5W
Auto Off/Sleep Mode – 110V	0.9W	0.8W	1.1W
Auto Off/Sleep Mode – 220V	0.9W	0.8W	1.1W
Power Off Mode – 110V	0.1W		
Power Off Mode – 220V	0.1W		
Default Time to Sleep Mode	15 min (as per Energy Star)		
Recovery from Sleep/Warm-up from Sleep	70 to 90 seconds		
Warm-up from Off	70 to 90 seconds		
OPERATING ENVIRONMENT			
Required Temperature Range – Fahrenheit (storage/shipping)	-40 to 104 °F		
Required Temperature Range – Fahrenheit (operating)	50 to 90 °F		
Required Temperature Range – Celsius (storage/shipping)	-40 to 40 °C		
Required Temperature Range – Celsius (operating)	10 to 32.2 °C		
Required Relative Humidity	8% to 80% RH		
SOUND POWER LEVELS			
Sound Pressure Levels	Operating simplex/duplex 53/50 dB(A) Quiet mode simplex/duplex 49/46 dB(A) Idle 14 dB(A)	Operating simplex/duplex 53/50 dB(A) Quiet mode simplex/duplex 48/46 dB(A) Idle 14 dB(A)	Operating simplex/duplex 53/50 dB(A) Quiet mode simplex/duplex 48/46 dB(A) Idle 14 dB(A)
Sound Power Levels	Operating simplex/duplex 68/64 dB(A) Quiet mode simplex/duplex 62/61 dB(A) Idle 31 dB(A)	Operating simplex/duplex 67/64 dB(A) Quiet mode simplex/duplex 63/61 dB(A) Idle 31 dB(A)	Operating simplex/duplex 68/64 dB(A) Quiet mode simplex/duplex 63/61 dB(A) Idle 31 dB(A)
DIMENSIONS AND WEIGHTS			
ENGINES (UNPACKAGED)			
Width (in)	14.5 in	16.2 in	
Depth (in)	14.3 in	14.4 in	
Height (in)	8.2 in	13.3 in	
Weight (lb)	20.6 lb	28.2 lb	
Width (mm)	368 mm	411 mm	
Depth (mm)	363 mm	366 mm	
Height (mm)	222 mm	339 mm	
Weight (kg)	9.3 kg	12.8 kg	
550 SHEET TRAY (UNPACKAGED)			
Width (in)	14.6 in		
Depth (in)	14.9 in		
Height (in)	4.2 in		
Weight (lb)	8.9 lb		
Width (mm)	370 mm		
Depth (mm)	378 mm		
Height (mm)	107 mm		
Weight (kg)	4.1 kg		

Xerox B310 Printer and Xerox B305/B315 Multifunction Printer

SYSTEM SPECIFICATION	XEROX B310 PRINTER	XEROX B305 MULTIFUNCTION PRINTER	XEROX B315 MULTIFUNCTION PRINTER
DIMENSIONS AND WEIGHTS (CONTINUED)			
ENGINES (PACKAGED)			
Width (in)	16.1 in	16.5 in	
Depth (in)	16.5 in	18.3 in	
Height (in)	11 in	15.1 in	
Weight (lb)	23.9 lb	32.4 lb	
Width (mm)	410 mm	420 mm	
Depth (mm)	420 mm	465 mm	
Height (mm)	280 mm	385 mm	
Weight (kg)	10.5 kg	14.7 kg	
550 SHEET TRAY (PACKAGED)			
Width (in)	16.9 in		
Depth (in)	17.6 in		
Height (in)	7.4 in		
Weight (lb)	10.8 lb		
Width (mm)	430 mm		
Depth (mm)	448 mm		
Height (mm)	188 mm		
Weight (kg)	4.9 kg		
INSTALLATION CONSIDERATIONS			
Clear area around the device is necessary for access and ventilation. The below table shows the area needed on each side for correct installation.			
Top	12 in/305 mm		
Rear	3 in/76.2 mm		
Left	4.33 in/110 mm		
Right	3.94 in/100 mm		
Front	12 in/305 mm		
SYSTEM CERTIFICATION/REGULATORY COMPLIANCE			
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertifications		
WHAT'S IN THE BOX			
All items contained in the box	B310 Printer Power Cord Installation Guide Product Safety Sheet Quick Use Guide Software and Documentation CD Pre-installed Starter Toner Cartridge: 2,500 page capacity ⁴	B305 Multifunction Printer Power Cord Installation Guide Product Safety Sheet Quick Use Guide Software and Documentation CD Pre-installed Starter Toner Cartridge: 1,500 page capacity ⁴	B315 Multifunction Printer Power Cord Installation Guide Product Safety Sheet Quick Use Guide Software and Documentation CD Pre-installed Starter Toner Cartridge: 2,500 page capacity ⁴

Xerox B310 Printer and Xerox B305/B315 Multifunction Printer

SUPPLIES AND ACCESSORIES	XEROX B310 PRINTER	XEROX B305 MULTIFUNCTION PRINTER	XEROX B315 MULTIFUNCTION PRINTER
SUPPLIES – NORTH AMERICA AND EUROPE*			
Genuine Xerox Black Standard Capacity Toner Cartridge (3,000 Pages) ⁴	006R04376		
Genuine Xerox Black High Capacity Toner Cartridge (8,000 Pages) ⁴	006R04377		
Genuine Xerox Black Extra High Capacity Toner Cartridge (20,000 Pages) ⁴	006R04378		
Imaging Kit (40,000 Pages) ⁵ Universal World Wide	013R00690		
SUPPLIES – ALL OTHER REGIONS			
Genuine Xerox Black Standard Capacity Toner Cartridge (3,000 Pages) ⁴	006R04379		
Genuine Xerox Black High Capacity Toner Cartridge (8,000 Pages) ⁴	006R04380		
Genuine Xerox Black Extra High Capacity Toner Cartridge (20,000 Pages) ⁴	006R04381		
Imaging Kit (40,000 Pages) ⁵ Universal World Wide	013R00690		
OPTIONAL ACCESSORIES			
550 Sheet Tray	497N07968		

* North America (NA): U.S., Canada

Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland Andorra, Azores, Corsica, Greenland, Iceland, Lichtenstein, Luxembourg, Madeira, San Marino

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Some functionality may require software update from xerox.com available Q4 2021.

⁴ Average standard pages. Declared yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁵ Approximate pages. Declared yield will vary depending on job run length and media size/orientation and print mode. For more information, visit office.xerox.com/latest/SUPGL-01.PDF

For more information, visit us at xerox.com/office.

Xerox® B410 Printer



Work doesn't slow down,
and your printer shouldn't either.

PRINT SPEED (UP TO:)	
One-sided Speed¹	Black-and-White: Up to 50/47 ppm Letter/A4
Two-sided Speed¹	Black-and-White: Up to 25/24 ppm Letter/A4
Monthly Duty Cycle² (Up To:) Pages Per Month	175,000
Recommended Average Monthly Print Volume (Up To:) Pages Per Month	20,000
Processor/Memory/Storage Clock Speed/Cores Memory/Storage	1 GHz Dual Core Processor 1GB RAM 8GB eMMC/ Optional: 500+GB HDD
Connectivity Device Connectivity	Hi-Speed USB 2.0 (Type A), Hi-Speed USB (Type B) Gigabit Ethernet/ Optional: Wireless Network Adapter (802.11 b/g/n/ac)
Imaging Technology	Laser
PRINT	
Print Resolution (Up To:)	1200 x 1200 dpi, 2400 Image Quality
First-Print-Out Time (As Fast As:)	As fast as 5.4 seconds black-and-white
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL 5 Emulation, PDF v1.7 Emulation, Direct Image
Print Features	One Touch UI, Print Quality, Normal, Secure, Saved and Sample Set Job Types, Duplex, Orientation, Collation, Print Job ID in Margins, Draft Mode, N-up, Booklet Layout, Watermark, Tray and Toner Status, Rotate Image 180 Degrees, Saved Settings, Earth Smart Settings
MOBILE AND CLOUD READY	
Mobile Printing	Apple AirPrint, Mopria Print Service, Chromebook, Wi-Fi Direct ³
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox Workplace Cloud and Suite is the complete print management platform for security, cost control and mobility delivering workflow productivity to office and hybrid workers. Available as an on-premises version (Workplace Suite) or a Cloud-based (Workplace Cloud), it provides the ultimate flexibility in freeing up IT teams to focus on core business priorities. (Select models may require additional optional equipment.)
Cloud Connectivity	Yes (via Xerox Print and Scan Experience)

Xerox B410 Printer

PRINT DETAILS	
First-Print-Out Time – B&W (As Fast As:)	5.2 seconds
Resolution (Up To:)	1200 x 1200 dpi, 2400 Image Quality
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL 5 Emulation, PDF v1.7 Emulation, Direct Image
Unprintable Page Margin	Print: 4.2 mm from each edge
Print from USB	Yes. Documents; PDF, HTML, XPS, Microsoft file formats (.doc, .docx, .xls, .xlsx, .ppt, .pptx) Images: .dcx, .gif, .JPEG (.jpg), .bmp, .pcx, .TIFF (.tif), .png
Print Driver Types/Operating Systems	Windows® 11, Windows® 10, Windows Server 2022, Windows Server 2019, Windows Server 2016, Windows Server 2012 R2, Windows Server 2012, macOS 13.x, macOS 12.x, macOS 11.x. Microsoft Universal Print. For the latest information about supported Operating Systems, please visit our Drivers & Downloads page and specify your device at support.xerox.com .
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD-Print, 802.1x, SNMP, ThinPrint, Universal Print, Bonjour
Font Capability	PCL5/6 94 scalable fonts, 2 bitmapped PS emulation 163 scalable fonts
DEVICE MANAGEMENT	
Device Management	Xerox Easy Assist, Remote Operator Panel, Embedded Web Server
Xerox® CentreWare® Web Software	Yes
SECURITY	
Security Protocols/Features	Digitally Signed Firmware Updates, Trusted Platform Module (TPM), TLS 1.3, FIPS 140-2 Certificate Management, Secure Password Reset, TCP Connection Filtering, Port Filtering, Access Controls, Confidential Print, Non-Volatile Memory Wipe, Protected USB Ports, IPSec, Image Overwrite ⁴
WI-FI SECURITY (REQUIRES WIRELESS NETWORK ADAPTER)	
Authentication and Encryption Methods	Infrastructure (BSS) Mode, WEP Encryption (64 & 128 bit keys), WPA2/WPA Personal AES PSK, WPA2-Personal, WPA3 Support, 802.1x; EAP-MD5, EAP-MSCHAPv2, EAP-TLS, EAP-TTLS (CHAP/MSCHAP/MSCHAPv2/PAP), LEAP, PEAP
PAPER HANDLING	
MAIN TRAY	
Standard/Optional	Standard
Capacity (Up To:)	550 sheets of 20 lb bond/75 gsm
Minimum Media Size (in)	4.1 x 5.8 in
Minimum Media Size (mm)	105 x 148 mm
Maximum Media Size (in)	Legal (8.5 x 14 in)
Maximum Media Size (mm)	216 x 360 mm
Minimum Media Weight (gsm)	60 gsm
Minimum Media Weight – Duplex (gsm)	60 gsm
Maximum Media Weight (gsm)	120 gsm
Maximum Media Weight – Duplex (gsm)	120 gsm
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Recycled, Bond, Labels, Pre-Printed, Colored Paper, Rough Cotton, Custom
BYPASS TRAY	
Standard/Optional	Standard
Capacity (Up To:)	100 sheets of 20 lb bond/75 gsm
Minimum Media Size (in)	3 x 5.8 in
Minimum Media Size (mm)	76 x 148 mm
Maximum Media Size (in)	Legal (8.5 x 14 in)
Maximum Media Size (mm)	216 x 360 mm
Minimum Media Weight (gsm)	60 gsm
Minimum Media Weight – Duplex (gsm)	60 gsm
Maximum Media Weight (gsm)	216 gsm
Maximum Media Weight – Duplex (gsm)	120 gsm
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Cardstock, Recycled, Bond, Labels, Glossy, Vinyl, Pre-Printed, Envelope, Colored Paper, Rough Cotton, Custom

Xerox B410 Printer

PAPER HANDLING (CONTINUED)	
OPTIONAL 550-SHEET TRAY (ADD UP TO 3 ADDITIONAL TRAYS)	
Capacity (Up To:)	550 sheets of 20 lb bond/75 gsm
Minimum Media Size (in)	4.1 x 5.8 in
Minimum Media Size (mm)	105 x 148 mm
Maximum Media Size (in)	Legal (8.5 x 14 in)
Maximum Media Size (mm)	216 x 360 mm
Minimum Media Weight (gsm)	60 gsm
Minimum Media Weight – Duplex (gsm)	60 gsm
Maximum Media Weight (gsm)	120 gsm
Maximum Media Weight – Duplex (gsm)	120 gsm
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Recycled, Bond, Labels, Pre-Printed, Colored Paper, Rough Cotton, Custom
STANDARD/MAXIMUM INPUT CAPACITY	
Standard Input Capacity	650
Maximum Input Capacity	2300
OUTPUT CAPACITY	
Output Capacity	250

Xerox B410 Printer

DEVICE SPECIFICATIONS	
ELECTRICAL REQUIREMENTS	
North America	100 to 127 volts (V) at 50 to 60 hz or 57 to 63 hertz (HZ) nominal 90 to 140 volts, extreme
Europe	220 to 240 volts (V) at 50 to 60 hz or 57 to 63 hertz (HZ) nominal (not available in all countries) 198 to 264 volts, extreme
POWER CONSUMPTION	
Operation/Running – 110V/220V	Simplex 669W; Duplex 417W
Standby Mode – 110V/220V	7.7W
Auto Off/Sleep Mode – 110V/220V	1.0W
Power Off Mode – 110V/220V	0.1W
Default Time to Sleep Mode	15 minutes (Adjustable 1-60 minutes)
Time to First Print from Sleep Mode	6.9 seconds
Time to Ready from Off	98 seconds
OPERATING ENVIRONMENT	
Required Temperature Range – Fahrenheit (operating)	50 to 90° F
Required Temperature Range – Celsius (operating)	10 to 32° C
Required Relative Humidity	8% to 80% RH
Required Temperature Range – Fahrenheit (storage)	-40 to 104° F
Required Temperature Range – Celsius (storage)	-40 to 40° C
SOUND POWER LEVELS	
Sound Pressure Levels	Operating simplex/56 dB(A) Operating duplex/55 dB(A) Quiet mode simplex/52 dB(A) Quiet mode duplex/51 dB(A) Idle 14 dB(A)
Sound Power Levels	Operating simplex/7.1 B(A) Operating duplex/6.9 B(A) Quiet mode simplex/6.6 B(A) Quiet mode duplex/6.6 B(A) Idle 3.1 B(A)

Xerox B410 Printer

DIMENSIONS AND WEIGHTS	
Printer (Packaged)	Width: 16.9 in/430 mm Depth: 18.5 in/470 mm Height: 16.6 in/422 mm Weight: 38 lb/17.2 kg
Printer (Unpackaged)	Width: 15.7 in/399 mm Depth: 14.7 in/373 mm Height: 12.1 in/308 mm Weight: 33.4 lb/15.2 kg
550-Sheet Tray (Packaged)	Width: 16.9 in/428mm Depth: 18.4 in/468 mm Height: 7.6 in/193 mm Weight: 12.2 kg/5.5 kg
550-Sheet Tray (Unpackaged)	Width: 15.3 in/389 mm Depth: 14.7 in/373 mm Height: 4.3 in/108 mm Weight: 10.4 lb/4.7 kg
Printer Stand (Packaged)	Width: 20.7 in/525 mm Depth: 22.2 in/565 mm Height: 9.2 in/235 mm Weight: 37.7 lb/17.1 kg
Printer Stand (Unpackaged)	Width: 18.2 in/463 mm Depth: 20 in/510 mm Height: 17.3 in/440 mm Weight: 32.7 lb/14.8 kg
INSTALLATION CONSIDERATIONS	
Clear area around the device is necessary for access and ventilation. The below table shows the area needed on each side for correct installation.	
Top	3.9 in/100 mm
Rear	3.9 in/100 mm
Left	2.6 in/65 mm
Right	4.3 in/110 mm
Front	12 in /305 mm
SYSTEM CERTIFICATION/REGULATORY COMPLIANCE	
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertifications
WHAT'S IN THE BOX	
All items contained in the box	B410 Printer Power Cord Installation Guide Product Safety Sheet Quick Use Guide Software and Documentation CD Pre-installed Starter Capacity Print Cartridges: Black cartridge: 6,000 print capacity ⁵

Xerox B410 Printer

SUPPLIES AND ACCESSORIES	NORTH AMERICA AND EUROPE*	ALL OTHER REGIONS
Genuine Xerox Black Standard Capacity Toner Cartridge, Xerox B410 Printer (6,000 Pages) ⁵	006R04725	006R04728
Genuine Xerox Black High Capacity Toner Cartridge, Xerox B410 Printer (14,000 Pages) ⁵	006R04726	006R04729
Genuine Xerox Black Extra High Capacity Toner Cartridge, Xerox B410 Printer (25,000 Pages)	006R04727	006R04730
Genuine Xerox Black Imaging Kit, Xerox B410 Printer (75,000 Pages) ⁶	013R00702	013R00702
OPTIONAL ACCESSORIES		
550-Sheet Tray	097N02469	
Wireless Network Adapter	097N02470	
500+GB Hard Disk	097N02467	
Xerox Printer Stand	097S05244	

* North America (NA): U.S., Canada
 Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland Andorra, Azores, Corsica, Greenland, Iceland, Lichtenstein, Luxembourg, Madeira, San Marino

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Requires Wireless Network Adapter

⁴ Requires 500+GB Hard Disk

⁵ Average standard pages. Declared yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

⁶ Approximate pages. Declared yield will vary depending on job run length and media size/orientation and print mode. For more information, visit office.xerox.com/latest/SUPGL-01.PDF

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. Visit xerox.com/About-Xerox/Recycling.

For more information, visit us at xerox.com/office.

Xerox® VersaLink® B610 Printer

VersaLink® B610 Printers are built on Xerox® ConnectKey® Technology.
For more information, go to www.ConnectKey.com.



SYSTEM SPECIFICATIONS	VERSALINK® B610
One-sided Speed¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 65 ppm black-and-white Up to 63 ppm black-and-white Up to 54 ppm black-and-white
Two-sided Speed¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 58.5 ppm black-and-white Up to 56 ppm black-and-white Up to 30.1 ppm black-and-white
Monthly Duty Cycle²	Up to 300,000 pages/month
Recommended Average Monthly Print Volume³	Up to 30,000 pages
Hard Drive	Optional 320 GB HDD
Processor	1.05 GHz ARM Dual Core
Memory	2 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11 n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3% Hz, 12 A			
Europe and Other Geographies	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3% Hz, 8 A			
POWER CONSUMPTION				
Continuous Print⁴	Maximum: 900 watts or less			
Ready (Standby)⁴	72 watts or less			
Energy Saver (Sleep Mode)⁴	0.79 watts or less			
Power Off Mode⁴	220-240 VAC: 0.3 watts or less 110-127 VAC: 0.2 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	32° to 95° F/0° to 35° C			
Required Temperature Range (Operating)	50 to 90° F/10 to 32° C			
Required Relative Humidity	15% to 85%			
Sound Power Levels Running Standby	70 dB(a) or less 42 dB(a) or less			
Sound Pressure Levels Running Standby	56.8 dB(a) or less 27.1 dB(a) or less			
Boot Time (from Off to UI Ready)	Less than 79 seconds			
Warm-up Time (from Sleep to UI Ready)	Less than 47 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
Base Unit	16.8 in./427.4 mm	18.3 in./465.5 mm	17.5 in./443.4 mm	49.2 lb./22.3 kg
Base Unit with Additional 550-sheet Tray	16.8 in./427.4 mm	18.3 in./465.5 mm	22.3 in./566.4 mm	63.8 lb./28.9 kg
Base Unit with High Capacity Feeder	16.8 in./427.4 mm	18.3 in./465.5 mm	35.5 in./902.4 mm	92.5 lb./42 kg
Base Unit with High Capacity Feeder and Finisher	16.8 in./427.4 mm	18.3 in./465.5 mm	45.3 in./1150.4 mm	107.5 lb./48.8 kg
Base Unit with High Capacity Feeder and Mailbox	16.8 in./427.4 mm	18.3 in./465.5 mm	45.3 in./1150.4 mm	104.2 lb./47.3 kg
550-sheet Tray	16.5 in./420 mm	10.4 in./464.5 mm	4.8 in./123 mm	14.6 lb./6.6 kg
High Capacity Feeder (includes Caster Base)	28.5 in./724.2 mm	30.4 in./772.1 mm	18 in./459 mm	43.3 lb./19.7 kg
Cabinet (includes Caster Base)	28.5 in./724.2 mm	30.4 in./772.1 mm	13.2 in./336 mm	37 lb./16.6 kg
Caster Base	28.5 in./724.2 mm	30.4 in./772.1 mm	3.5 in./90 mm	18.7 lb./8.5 kg
Mailbox	17.7 in./450.8 mm	18.8 in./477.6 mm	9.8 in./248.0 mm	11.7 lb./5.3 kg

Xerox® VersaLink® B610 Printer

Finisher	17.7 in./450.8 mm	16.2 in./411.0 mm	9.8 in./248.0 mm	15 lb./6.8 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
Base Unit	22.8 in/580 mm	25 in/634 mm	23.9 in/607 mm	61.6 lb./28 kg
550-sheet Tray	21 in/535 mm	23 in/584 mm	9.8 in/248 mm	18.7 lb./8.5 kg
High Capacity Feeder (includes Caster Base)	22.4 in/568 mm	26.1 in/663 mm	28 in/711 mm	79.4 lb./38 kg
Cabinet (includes Caster Base)	23 in/584 mm	24.8 in/629 mm	23.5 in/597 mm	57.3 lb./28 kg
Caster Base	23 in/585 mm	24.4 in/619 mm	13 in/330 mm	39.7 lb./18 kg
Mailbox	22.6 in/573 mm	20.4 in/518 mm	15.2 in/386 mm	16.3 lb./7.8 kg
Finisher	22.6 in/573 mm	15.7 in/398 mm	15.2 in/386 mm	18.6 lb./8.8 kg
Wireless Network Adapter (Wi-Fi Kit)	7.4 in/188 mm	5.4 in/136 mm	2.2 in/55 mm	1.05 lb./0.1 kg
Hard Drive	4.5 in/116 mm	1.8 in/46 mm	7 in/178 mm	0.4 lb./0.18 kg
CERTIFICATIONS				
To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .				
PRINT				
First-Print-Out Time	As fast as 3.7 seconds			
Print Resolution	Up to 1200 x 1200 dpi			
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
Maximum Print Area	4 mm from Lead edge of paper, 2 mm from Side and Trail edges of paper			

Xerox® VersaLink® B610 Printer

<p>Print Features</p>	<p>Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing Watermark (predefined and custom) Earth Smart Driver Settings</p>
<p>Print from USB</p>	<p>Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</p>
<p>Operating Systems</p>	<p>Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP®</p> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com</p>
<p>Fonts</p>	<p>PostScript fonts: 136 PCL fonts: 83</p>
<p>Xerox® Global Print Driver®</p>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<p>Xerox® Pull Print Driver</p>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>

SOFTWARE SOLUTIONS	
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.
MOBILE SOLUTIONS AND MOBILE DEVICE APPS	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopria® Certified	ConnectKey® Technology-enabled print devices are Mopria certified. Mopria certification ensures you can print wirelessly from your Mopria supported (Android) smart phone, tablet and other mobile devices instantly and easily.
Xerox® @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Easy Assist App	The Xerox® Easy Assist app simplifies installation, monitoring and management of your printer or MFP right from your mobile phone. It provides easy access to self-support services and real-time monitoring of printer performance. And, Xerox® Smart Start Software takes the guess work out of setup by automating the installation of the latest software for your printer or MFP on your computer – all without IT support – allowing you to be up and running quickly.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.
SECURITY	
Security Features	<ul style="list-style-type: none"> Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS 1.3/SSL Trusted Platform Module (TPM) <p>*Requires HDD/Productivity Kit</p>

ACCOUNTING	
XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)	
Tracking	Print usage
Accounting	<p>Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts</p> <p>Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)</p>
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	<ul style="list-style-type: none"> • Enhanced network accounting with up to the minute data on how the system is being used • Comprehensive management and enterprise scale tracking and reporting of printusage • Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com • Security enhancements include simultaneous support for HTTP/HTTPS protocols • Device requests account authentication from third party server enabling larger databases of users and accounts • Accept Authentication Login at control panel and pass to third party NetworkingAccount • Interface with third party accounting terminal for accounting user interface
PAPER HANDLING	
BYPASS TRAY	
Capacity⁵	150 sheets
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in./76 x 127 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
Media Types	Plain Paper Bond Punched Pre-Printed Recycled Envelopes Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5
TRAY 1	
Capacity⁵	550 sheets
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76.2 x 190 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm

Media Types	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5
UP TO 4 ADDITIONAL TRAYS	
Capacity⁵	550 sheets
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76.2 x 190 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
Media Types	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5
HIGH CAPACITY FEEDER (CAN BE COMBINED WITH UP TO 1 ADDITIONAL TRAY)	
Capacity⁵	2,000 sheets
Sizes	Standard sizes: A4 SEF, Letter SEF
Weights One-sided: Two-sided:	16 lb. bond to 65 lb. cover/60 to 176 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
Types	Plain Paper Bond Punched Pre-Printed Recycled Lightweight Cardstock Letterhead Custom 1 - 5
TOTAL PAPER CAPACITY⁵	
Base Unit	700 sheets
Base Unit with Additional 550-sheet Tray	1,250 sheets
Base Unit with High Capacity Feeder	2,700 sheets
Base Unit with High Capacity Feeder and Finisher	2,700 sheets
Base Unit with High Capacity Feeder and Mailbox	2,700 sheets
Maximum Paper Capacity	3,250 sheets

PAPER OUTPUT	
OUTPUT TRAY	
Capacity⁵	500 sheets with tray full sensor (without Finisher or Mailbox)
Automatic Two-sided Printing	Standard
FINISHER	
Capacity⁵	500-sheet tray, 50-sheet stapling
MAILBOX	
Capacity⁵	Four 100-sheet bins
DEVICE MANAGEMENT	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint® Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS 1.3, SNTP, MDNS
REMOTE CONTROL PANEL	
	<ul style="list-style-type: none"> • Enables faster, more convenient technical support and user training • IT administrators and other authorized users can control the device remotely from a web page on any PC • Remote user experience is identical to performing tasks directly at the device
XEROX® CENTREWARE® WEB	
	<ul style="list-style-type: none"> • A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE	
Device Status	<ul style="list-style-type: none"> • Tray Status/Contents • Consumables Status • Billing/Usage • Quick Links • Online Support
Print Queue Viewing	Job print queue management — view and delete
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
REMOTE SERVICES	
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.

Xerox® VersaLink® B610 Printer

WHAT COMES IN THE BOX		
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
WHAT COMES IN THE BOX VersaLink® B600 Printer Standard Capacity Print Cartridge –Black: 10,300 print capacity ⁶ Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord		
SUPPLIES		
Extra-High Capacity Toner Cartridge	Black: 46,700 standard pages ⁶	106R03944
High Capacity Toner Cartridge	Black: 25,900 standard pages ⁶	106R03942
Standard Capacity Toner Cartridge	Black: 10,300 standard pages ⁶	106R03940
Drum Cartridge	Black: 60,000 pages ⁷	101R00582
ACCESSORIES/OPTIONS		
2,000-sheet High Capacity Feeder (includes Caster Base)		097S04948
550-sheet Feeder		097S04949
Finisher (500 sheets, 50-sheet stapler)		097S04952
4-Bin Mailbox (100 sheets per bin)		097S04953
Caster Base		097S04954
Cabinet (includes stabilizers)		097S04994
Wireless Network Adapter (Wi-Fi Kit)		497K16750
Productivity Kit with 320 GB HDD		497K18360
RFID Card Reader Kit		497K18380

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program.

For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.